



GrüloLine

Water S/D 10**Rubber spiral hose**

Water S/D is ideally suited for construction, agriculture and industry, for irrigation and drainage. The core is resistant to sewage, slurry, drilling mud and slightly abrasive media. The abrasion-resistant cover offers a good resistance to weathering.

Technical characteristics

Norm: ISO 1307

Temperature range: -25 °C to +70 °C

Standard Length: 40 m | from DN 127: 20 m

Colour: Black

Construction

Cover: SBR, with fabric impression

Reinforcement: Synthetic textile, steel wire spiral

Lining: NR/SBR, black, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
25	1	5,00	10	30	0,9	153	0,697	10056-025
32	1 1/4	5,00	10	30	0,9	192	0,924	10056-032
45	1 3/4	5,00	10	30	0,9	267	1,440	10056-042
51	2	5,50	10	30	0,9	306	1,738	10056-051
76	3	6,50	10	30	0,9	458	2,845	10056-075
102	4	6,50	10	30	0,9	610	3,930	10056-102
127	5	8,50	10	30	0,9	762	6,140	10056-127
152	6	8,50	10	30	0,9	915	7,850	10056-152
203	8	11,00	10	30	0,9	1219	13,500	10056-203
254	10	12,50	10	30	0,9	1524	18,240	10056-254
305	12	12,00	10	30	0,9	1829	21,400	10056-305

Reliable, for sure!