



GrüloLine

Sandblast

Shot blast hose

Premium rubber sandblaster hose with long durability due to high abrasion resistance tube (DIN 53516 < 35 mm³), confirmed by German Institute of Rubber Technology (DIK). **Sandblast** is torsion-free, kink resistant and electrical conductive.

Technical characteristics

Temperature range: -35 °C to +80 °C

Standard Length: 40 m

Colour: Black

Construction

Cover: NR/SBR, antistatic, fabric impression

Reinforcement: Textile wrapped

Lining: NR/BR, smooth, electrically conductive

Marking: G+L Ellipse SANDBLAST PN 12 bar

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
13	1/2	7,00	12	36	130	0,500	10116-013
19	3/4	7,00	12	36	190	0,650	10116-019
25	1	7,00	12	36	250	0,800	10116-025
32	1 1/4	8,00	12	36	320	1,150	10116-032
38	1 1/2	9,00	12	36	380	1,525	10116-038
42	-	9,00	12	36	420	1,700	10116-042
51	2	9,00	12	36	500	2,000	10116-051



We gladly assemble
your hose with the
suitable coupling

Reliable, for sure!