



GrüloLine

GrüloChem SP EPDM

EPDM Chemical hose

Suitable as suction and discharge hose in the chemical industry as well as for sea water and industrial waste water. Cover and lining are electrically conductive ($R \leq 10^6 \Omega/m$).

Technical characteristics

Norm: EN 12115

Temperature range: -20 °C to +100 °C

Standard Length: 40 m

Colour: Black

Construction

Cover: CR, fabric impressions

Reinforcement: Textile cord with two steel spirals and two copper litz wires

Lining: EPDM, Black

Marking: GrüloChem SP EPDM EN 12115

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
19	3/4	6,00	16	64	0,92	125	0,633	10164-019
25	1	6,00	16	64	0,92	150	0,781	10164-025
32	1 1/4	6,00	16	64	0,92	175	1,027	10164-032
38	1 1/2	6,50	16	64	0,92	225	1,416	10164-038
51	2	8,00	16	64	0,92	275	2,203	10164-051
76	3	8,00	16	64	0,80	350	3,159	10164-076
102	4	8,00	16	64	0,80	450	4,360	10164-102

Reliable, for sure!