



GrüloVent

PVC suction hose, flame retardant

PVC hose with a rigid PVC spiral, designed for the extraction of air-solid mixtures, cable protection and other protective applications, and liquid drainage. The **GrüloVent** features a robust construction and a very smooth flow channel. This hose is flame-retardant in accordance with UL94V0.

Technical characteristics

Norm: UL94 V0

Temperature range: -5 °C to +60 °C

Standard Length: 25 m | from DN 110: 10 m

Colour: Grey

Construction

Cover: PVC, corrugated

Reinforcement: Hard PVC spiral

Material: Soft PVC, smooth

Inner-Ø mm	Material thickness mm	WP bar	Vacuum bar	Bending radius mm	Weight/m kg	Article no.
51	0,90	1,30	0,50	75	0,410	10214-051
76	1,00	1,10	0,40	113	0,700	10214-076
80	1,00	1,00	0,40	120	0,730	10214-080
90	1,00	1,00	0,40	135	0,780	10214-090
100	1,00	1,00	0,40	150	0,980	10214-100
110	1,00	0,90	0,40	165	1,100	10214-110
120	1,00	0,70	0,35	180	1,280	10214-120
127	1,00	0,70	0,35	188	1,300	10214-127
152	1,10	0,50	0,35	225	1,700	10214-152
160	1,20	0,50	0,35	240	1,820	10214-160
200	1,30	0,30	0,30	300	2,170	10214-200
250	1,50	0,30	0,30	375	3,400	10214-250
280	1,50	0,30	0,25	390	3,500	10214-280
300	1,50	0,30	0,20	400	3,600	10214-300

All technical information refer to a temperature of 23 °C.

Reliable, for sure!