



GruloPipe

Pipe cleaning hose

GruloPipe out of our product line GruloLine offers all benefits of a premium high pressure rubber hose. **GruloPipe** is extremely flexible, abrasion-, pressure- and oil resistant. With its WP of 250 bar **GruloPipe** is suited perfectly for the application on jetting lances, used for the cleaning of manholes and provisional cleaning of house connections.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

GruloLine

Technical characteristics

Norm: EN 853 1 SN (R1 AT)

Temperature range: -40 °C up to +90 °C

Standard Length: 40 m, 60 m, 80 m, 100 m, 120 m, 240 m

Availability: 40 m up to 240 m

Colour: Black

Construction

Cover: SBR, very smooth

Reinforcement: Highly tear resistant steel wire braid

Lining: SBR, black, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
10	3/8	4,00	250	640	130	0,320	10550-009
13	1/2	4,00	250	640	180	0,420	10550-013
16	5/8	4,00	250	640	210	0,520	10550-016
19	3/4	4,00	200	600	240	0,710	10550-019



Reliable, for sure!