


GrüloLine

GrüloKan 250 Premium

Outstanding abrasion resistance

GrüloKan 250 Premium offers you much more than all common rubber sewer cleaning hoses. The especially developed composite bilayers structure of the cover enables a very high abrasion resistance according to EN ISO 6945 (50 N and 2000 cycles max. 1g). This guarantees you a long lifetime at equal flexibility in comparison to our classic **GrüloKan 250**. Therefore our **GrüloKan 250 Premium** can be used in any situation, where all others fail.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Norm: EN ISO 6945

Temperature range: -40 °C to + 70 °C

Standard Length: 80 m, 120 m, 160 m | further lengths on request

Availability: 10 m up to 240 m | DN 32 up to 180 m

Colour: Black

Construction

Cover: NR/SBR rubber with plastic coating, extremely abrasion resistant

Coating: Composite bi-layers structure with outstanding abrasion resistance

Reinforcement: 2-ply braided synthetic fibres

Lining: NR/SBR, black, smooth

Marking: Transfer tape [Ellipse G+L] GrüloKan Premium WP 250 bar BP 625 bar

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	7,00	250	625	110	0,775	10866-025
32	1 1/4	8,00	250	625	140	1,095	10866-032

Reliable, for sure!