



GrüloLine

GrüloJet 250 Performance

PU sewer jetting hose, 250 bar

GrüloJet 250 Performance features a pressure-bearing layer made of double-braided, highly tear-resistant synthetic fibres and a thermoplastic core. This guarantees an exceptionally long service life and reduces your operating costs. It is buoyant, abrasion- and cut-resistant, and highly flexible. Thanks to its extremely smooth inner tube, it experiences less pressure loss than standard rubber sewer cleaning hoses. Its improved material composition compared to the GrüloJet 250 guarantees high wear resistance.

The hose includes DKR/AGR (IG/AG) BSP 60° press-fittings on both ends with a self-sealing design, and comes with a test certificate in accordance with EN 10204 3.1B. We are also happy to offer other connection options as a service!

Technical characteristics

Temperature range: -40 °C to +55 °C

Standard Length: 200 m, 240 m

Colour: Light green

Construction

Cover: Polyurethane, extremely cut- and abrasion resistant

Reinforcement: Highly tear resistant double textile fibre braids

Lining: Thermoplastic elastomer

Marking: -  - *GrüloJet 250 Performance* -  - DN [...] | WP 250 bar | BP 625 bar | [Datum]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	5,85	250	625	150	0,650	10889-025

Reliable, for sure!