



Suction Hose Couplings with security collar according DIN 2817-3, without clamps

Page 1

Material: Aluminium**Dichtung:** Nitrile caoutchouc, black or white**Working pressure:** 16 bar**Material:** Stainless steel**Dichtung:** Viton**Working pressure:** 16 bar

Storz	Lug mm	Female thread Inch	Aluminium			Stainless steel	
			Remark	Weight/piece kg	Article no.	Weight/piece kg	Article no.
25-D	31	1/2	-	0,080	21020-025-04-01	0,270	21020-025-04-13
		3/4	-	0,080	21020-025-06-01	0,250	21020-025-06-13
		1	DIN 14 306	0,080	21020-025-10-01DIN	0,210	21020-025-10-13
32	44	1	-	0,160	21020-032-10-01	-	-
		1 1/4	-	0,140	21020-032-12-01	-	-
38	51	1	-	0,150	21020-038-10-01	-	-
		1 1/4	-	0,170	21020-038-12-01	0,520	21020-038-12-13
		1 1/2	-	0,150	21020-038-14-01	0,470	21020-038-14-13
		2	-	0,180	21020-038-20-01	-	-
45	59	1 1/2	-	0,250	21020-045-14-01	-	-
		2	-	0,240	21020-045-20-01	-	-
52-C	66	3/4	-	0,290	21020-052-06-01	0,880	21020-052-06-13
		1	-	0,280	21020-052-10-01	1,080	21020-052-10-13
		1 1/4	-	0,300	21020-052-12-01	1,020	21020-052-12-13
		1 1/2	-	0,280	21020-052-14-01	0,980	21020-052-14-13
		1 3/4	-	0,240	21020-052-16-01	-	-
		2	DIN 14 307	0,280	21020-052-20-01DIN	0,770	21020-052-20-13
		2 1/2	-	0,280	21020-052-24-01	1,540	21020-052-24-13

Storz	Lug mm	Female thread Inch	Aluminium			Stainless steel	
			Remark	Weight/piece kg	Article no.	Weight/piece kg	Article no.
65	81	1 1/2	-	0,450	21020-065-14-01	-	-
		2	-	0,380	21020-065-20-01	1,310	21020-065-20-13
		2 1/2	-	0,380	21020-065-24-01	1,020	21020-065-24-13
		3	-	0,410	21020-065-30-01	-	-
75-B	89	2	-	0,430	21020-075-20-01	1,500	21020-075-20-13
		2 1/2	DIN 14 308	0,420	21020-075-24-01DIN	1,510	21020-075-24-13
		3	-	0,420	21020-075-30-01	1,260	21020-075-30-13
90	105	3	-	0,600	21020-090-30-01	-	-
100	115	4	-	0,850	21020-100-40-01	2,220	21020-100-40-13
110-A	133	3	with reducer	1,430	21020-110-30-01	-	-
		4	-	1,090	21020-110-40-01	3,500	21020-110-40-13
		4 1/2	DIN 14 309	1,120	21020-110-44-01DIN	3,200	21020-110-44-13
		5	with cuff	1,390	21020-110-50-01	-	-
125	148	4	-	1,680	21020-125-40-01	-	-
		5	-	1,380	21020-125-50-01	3,550	21020-125-50-13
150	160	6	-	1,820	21020-150-60-01	5,300	21020-150-60-13
165	188	6	max. PN 10bar	2,160	21020-165-60-01	-	-
205	220	8	max. PN 10 bar	3,480	21020-205-80-01	-	-

Also available in brass.

